



4770-X-60 SHORT OIL ALKYD RESIN

4770-X-60 SHORT OIL ALKYD RESIN is a non-drying short oil alkyd resin containing coconut oil. Typical uses include plasticizer for nitrocellulose lacquers, and high quality low yellowing baking enamels with excellent durability.

SOLUTION PROPERTIES:

Non-volatile by weight	60 ± 1%
Non-volatile by volume	52 ± 1%
Weight per gallon @ 25°C	8.7 ± 0.1 pounds
Viscosity @ 25°C	Z ₁ – Z ₃
Reduced Viscosity @ 25°C (40% N.V. in Xylene)	B – E
Color (Gardner)	3 maximum
Flash Point (Seta)	81°F
Solvent	Xylene
Appearance	Clear, light yellow liquid

SOLID RESIN PROPERTIES:

Phthalic Anhydride	Present
Oil Type	Coconut
Oil Length	Short
Acid Value	12 maximum
Modifier(s)	None

7/1/99

While the information contained herein is deemed accurate, it is intended as a guide only and property values and ranges listed above should be regarded as typical values and should not be construed either as a product specification or as a guaranteed analysis for any specific lot of the product. All guarantees/warranties and other terms existing are exclusively contained in the Company's invoices and are effective only upon purchase of products.

ROUTE 993 ■ P. O. BOX 607 ■ MANOR, PA 15665 ■ (724) 864-8200 ■ FAX (724) 864-8232