



## **4845-BC-70 WATER REDUCIBLE ALKYD RESIN**

**4845-BC-70 WATER REDUCIBLE ALKYD RESIN** is a water reducible alkyd resin intended for use in air dry and force dry industrial finishes. It will give good corrosion and water resistance when properly formulated.

### **SOLUTION PROPERTIES:**

Non-volatile by weight	70 ± 1%
Non-volatile by volume	65 ± 1%
Viscosity @ 25°C	Z <sub>4</sub> – Z <sub>1</sub>
Weight per gallon @ 25°C	8.85 ± 0.1 pounds
Flash Point (Seta)	128°F
Color	8 Maximum
Solvent	2-Butoxy Ethanol

### **SOLID RESIN PROPERTIES:**

Acid Value	37-43
Oil Type	Mixed Drying
Oil Length	Short

### **DRIER RECOMMENDATION (% METAL BASED ON RESIN SOLIDS):**

0.05% -	0.8% Cobalt
0.10%	0.20% Zirconium

8/8/96

---

While the information contained herein is deemed accurate, it is intended as a guide only and property values and ranges listed above should be regarded as typical values and should not be construed either as a product specification or as a guaranteed analysis for any specific lot of the product. All guarantees/warranties and other terms existing are exclusively contained in the Company's invoices and are effective only upon purchase of products.

---

ROUTE 993 ■ P. O. BOX 607 ■ MANOR, PA 15665 ■ (724) 864-8200 ■ FAX (724) 864-8232