



**5023-V-60 MEDIUM OIL ALKYD**

**5023-V-60 MEDIUM OIL ALKYD** is suitable for use in traffic and road marking paints.

**SOLUTION PROPERTIES:**

Non-volatile by weight	60 ± 1.0%
Non-volatile by volume	51 ± 1.0%
Weight per gallon @ 25°C	7.66 ± 0.3 pounds
Viscosity @ 25°C	Z <sub>2</sub> – Z <sub>5</sub>
Appearance	Amber Liquid
Color, Gardner	10 maximum
Solvent	VM&P Naphtha
Flash Point (SETA)	40°F
Cure Type	Air/Bake

**SOLID RESIN PROPERTIES:**

Phthalic Anhydride	Present
Oil Type	Mixed Drying
Oil Length	Medium
Acid Value	10 maximum
Modifier(s)	None
OH Equivalent Weight	N/A

**DRIER RECOMMENDATIONS (% METAL BASED ON RESIN SOLIDS):**

0.05	-	0.10%	Cobalt
0.05	-	0.08%	Calcium
0.08	-	0.15%	Zirconium

2/22/06

---

While the information contained herein is deemed accurate, it is intended as a guide only and property values and ranges listed above should be regarded as typical values and should not be construed either as a product specification or as a guaranteed analysis for any specific lot of the product. All guarantees/warranties and other terms existing are exclusively contained in the Company's invoices and are effective only upon purchase of products.

---