



5150-BS-70 WATER REDUCIBLE ALKYD RESIN

5150-BS-70 WATER REDUCIBLE ALKYD RESIN is a fast drying chain-stopped water reducible alkyd resin intended for industrial and OEM finishes. It was formulated to be economical, but offers very good film properties at the same time.

SOLUTION PROPERTIES:

Non-volatile by weight	70 ± 1%
Non-volatile by volume	65 ± 1%
Weight per gallon @ 25°C	8.63 ± 0.15 pounds
Viscosity @ 25°C	Z ₄ – Z ₆
Flash Point (SETA)	98°F
Color (Gardner)	12 max.
Solvent(s) Present	2-Butanol/2-Butanol Ethanol
Cure Type	Air dry/force dry

SOLID RESIN PROPERTIES:

Phthalic Anhydride	Absent
Oil Type	Mixed Oxidizing
Oil Length	Short
Acid Value	41 - 49
Modifier(s)	None
OH Equivalent Weight	N/A

DRIER RECOMMENDATIONS (% METAL BASED ON RESIN SOLIDS):

0.06	-	0.12% Cobalt
0.05	-	0.15% Zirconium

9/26/05

While the information contained herein is deemed accurate, it is intended as a guide only and property values and ranges listed above should be regarded as typical values and should not be construed either as a product specification or as a guaranteed analysis for any specific lot of the product. All guarantees/warranties and other terms existing are exclusively contained in the Company's invoices and are effective only upon purchase of products.

ROUTE 993 ■ P. O. BOX 607 ■ MANOR, PA 15665 ■ (724) 864-8200 ■ FAX (724) 864-8232